



Construction: Glass Tube
 Rated current : 0.1A-30A
 Rated Voltage: 32V/125V
 Standard: UL, CSA

Electrical Characteristic

Rated Current	1 In	1.35 In	2 In
In	Min.	Max.	Max.
0.1A-30A	4 h	3600 S	120 S



FAG635-16 Series
Fast Acting, Glass Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
FAG635-16-0.100	100mA	10KA @ 125V/AC	125V
FAG635-16-0.125	125mA		
FAG635-16-0.250	250mA		
FAG635-16-0.375	375mA		
FAG635-16-0.500	500mA		
FAG635-16-0.600	600mA		
FAG635-16-0.750	750mA		
FAG635-16-001	1A		
FAG635-16-1.50	1.5A		
FAG635-16-002	2A		
FAG635-16-2.50	2.5A		
FAG635-16-003	3A		
FAG635-16-005	5A		
FAG635-16-006	6A	1000A @ 32V/AC	32V
FAG635-16-007	7A		
FAG635-16-7.50	7.5A		
FAG635-16-010	10A		
FAG635-16-015	15A		
FAG635-16-020	20A		
FAG635-16-025	25A		
FAG635-16-030	30A		