



Construction: Ceramic Tube

Rated current: 0.05A-30A

Rated Voltage: 125V/250V

Approvals: JIS C6575, 15A and less

Electrical Characteristic

Rated Current	1.3 In	1.6 In	2 In
	Min.	Max.	Max.
0.05A-30A	4 h	3600 S	120 S



NBC520 Series
Normal Blow, Ceramic Tube

Part Number	Rated Current	Breaking Capacity	Rated Volta		
NBC520-0.050-__	50mA	35A @ 250V/AC 10KA @ 250V/AC	125V/250V		
NBC520-0.060-__	60mA				
NBC520-0.063-__	1/16A				
NBC520-0.070-__	70mA				
NBC520-0.080-__	80mA				
NBC520-0.100-__	100Ma				
NBC520-0.125-__	125mA				
NBC520-0.160-__	160mA				
NBC520-0.200-__	200mA				
NBC520-0.250-__	250mA				
NBC520-0.300-__	300mA				
NBC520-0.315-__	315mA				
NBC520-0.400-__	400mA				
NBC520-0.500-__	500mA				
NBC520-0.600-__	600mA				
NBC520-0.630-__	630mA				
NBC520-0.700-__	700mA				
NBC520-0.800-__	800mA				
NBC520-001-__	1A			100A @ 250V/AC 10KA @ 125V/AC	
NBC520-1.25-__	1.25A				
NBC520-1.50-__	1.5A				
NBC520-1.60-__	1.6A				
NBC520-002-__	2A				
NBC520-2.50-__	2.5A				
NBC520-003-__	3A				
NBC520-3.15-__	3.15A				
NBC520-3.50-__	3.5A				
NBC520-004-__	4A	200A @ 250V/AC 10KA @ 125V/AC			
NBC520-005-__	5A				
NBC520-006-__	6A				
NBC520-6.30-__	6.3A				
NBC520-007-__	7A				
NBC520-008-__	8A				
NBC520-010-__	10A				
NBC520-012-__	12A			1000A @ 125V/AC	125V
NBC520-013-__	13A				
NBC520-015-__	15A	1000A @ 32V/AC/DC	32V		
NBC520-016-__	16A				
NBC520-020-__	20A				
NBC520-025-__	25A				
NBC520-030-__	30A				

Style Options: Nil = Axial w/o Leads
P = Radial Straight Leads
PA = Axial with Leads
PR = Radial Bent Leads
ex. NBC520-3.15-PR