



Construction: Glass Tube
 Rated current: 0.05A-30A
 Rated Voltage: 125V/250V
 Approvals: JIS C6575, 15A and less

Electrical Characteristic

Rated Current	1.3 In	1.6 In	2 In
In	Min.	Max.	Max.
0.05A-30A	4 h	3600 S	120 S



NBG520 Series
Normal Blow, Glass Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
NBG520-0.050-__	50mA	35A @ 250V/AC 10KA @ 250V/AC	125V/250V
NBG520-0.060-__	60mA		
NBG520-0.063-__	1/16A		
NBG520-0.070-__	70mA		
NBG520-0.080-__	80mA		
NBG520-0.100-__	100Ma		
NBG520-0.125-__	125mA		
NBG520-0.160-__	160mA		
NBG520-0.200-__	200mA		
NBG520-0.250-__	250mA		
NBG520-0.300-__	300mA		
NBG520-0.315-__	315mA		
NBG520-0.400-__	400mA		
NBG520-0.500-__	500mA		
NBG520-0.600-__	600mA		
NBG520-0.630-__	630mA		
NBG520-0.700-__	700mA		
NBG520-0.800-__	800mA		
NBG520-001-__	1A		
NBG520-1.25-__	1.25A		
NBG520-1.50-__	1.5A		
NBG520-1.60-__	1.6A		
NBG520-002-__	2A		
NBG520-2.50-__	2.5A		
NBG520-003-__	3A		
NBG520-3.15-__	3.15A		
NBG520-3.50-__	3.5A		
NBG520-004-__	4A		
NBG520-005-__	5A		
NBG520-006-__	6A		
NBG520-6.30-__	6.3A		
NBG520-007-__	7A		
NBG520-008-__	8A		
NBG520-010-__	10A		
NBG520-012-__	12A		
NBG520-013-__	13A		
NBG520-015-__	15A		
NBG520-016-__	16A		
NBG520-020-__	20A		
NBG520-025-__	25A		
NBG520-030-__	30A		
		100A @ 250V/AC 10KA @ 125V/AC	
		200A @ 250V/AC 10KA @ 125V/AC	
		1000A @ 32V/AC	32V

└─ Style Options: Nil = Axial w/o Leads
 P = Radial Straight Leads
 PA = Axial with Leads
 PR = Radial Bent Leads
 ex. NBG520-3.15-PR