



Construction: Ceramic Tube

Rated current: 0.1A-16A

Rated Voltage: 250V

Standard: IEC-127-2/1

Electrical Characteristic

In	1.5 In		2.1 In		2.75 In		4 In		10 In
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Max.
32mA-3A	1h	30min	0.01 s	2s	3ms	300 ms	20ms		
3.15A-6.3A	1h	30min	0.01 s	3s	3ms	300 ms	20ms		
8A-10A	30min	30min	0.01 s	3s	3ms	300 ms	20ms		



QAC520 Series
Quick Acting, Ceramic Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
QAC520-0.100-__	100mA	10,000A @ 125V/AC 35A @ 250V/AC	125V/250V
QAC520-0.125-__	125mA		
QAC520-0.160-__	160mA		
QAC520-0.200-__	200mA		
QAC520-0.250-__	250mA		
QAC520-0.300-__	300mA		
QAC520-0.315-__	315mA		
QAC520-0.400-__	400mA		
QAC520-0.500-__	500mA		
QAC520-0.600-__	600mA		
QAC520-0.630-__	630mA		
QAC520-0.700-__	700mA		
QAC520-0.800-__	800mA		
QAC520-001-__	1A		
QAC520-1.25-__	1.25A		
QAC520-1.50-__	1.5A		
QAC520-1.60-__	1.6A		
QAC520-002-__	2A		
QAC520-2.50-__	2.5A		
QAC520-003-__	3A		
QAC520-3.15-__	3.15A		
QAC520-004-__	4A		
QAC520-005-__	5A		
QAC520-006-__	6A		
QAC520-6.30-__	6.3A		
QAC520-007-__	7A		
QAC520-008-__	8A		
QAC520-010-__	10A		
QAC520-012-__	12A		
QAC520-013-__	13A		
QAC520-015-__	15A		
QAC520-016-__	16A		
QAC520-020-__	20A		

└─ Style Options: Nil = Axial w/o Leads
 PA = Axial with Leads
 PR = Radial Bent Leads
 ex. QAC520-3.15-PR