



Construction: Ceramic Tube

Rated current: 0.05A-30A

Rated Voltage: 125V/250V

Standard: UL248, CSA C22.2 248

Electrical Characteristic

Rated Current	1 In		2 In	
	Min.	Max.	Min.	Max.
0.05A-30A	4 h	3600 S	3 S	120 S



**SBC520 Series**  
**Slow Blow, Ceramic Tube**

Part Number	Rated Current	Breaking Capacity	Rated Voltage
SBC520-0.050-__	50mA	35A @ 250V/AC  10KA @ 125V/AC	125V/250V
SBC520-0.063-__	63mA		
SBC520-0.080-__	80mA		
SBC520-0.100-__	100mA		
SBC520-0.125-__	125mA		
SBC520-0.160-__	160mA		
SBC520-0.200-__	200mA		
SBC520-0.250-__	250mA		
SBC520-0.300-__	300mA		
SBC520-0.315-__	315mA		
SBC520-0.400-__	400mA		
SBC520-0.500-__	500mA		
SBC520-0.600-__	600mA		
SBC520-0.630-__	630mA		
SBC520-0.700-__	700mA		
SBC520-0.800-__	800mA		
SBC520-001-__	1A		
SBC520-1.25-__	1.25A		
SBC520-1.50-__	1.5A		
SBC520-1.60-__	1.6A		
SBC520-002-__	2A		
SBC520-2.50-__	2.5A		
SBC520-003-__	3A		
SBC520-3.15-__	3.15A		
SBC520-3.50-__	3.5A		
SBC520-004-__	4A	200A @ 250V/AC  10KA @ 125V/AC	125V/250V
SBC520-005-__	5A		
SBC520-006-__	6A		
SBC520-6.30-__	6.3A		
SBC520-007-__	7A		
SBC520-008-__	8A		
SBC520-010-__	10A		
SBC520-012-__	12A		
SBC520-013-__	13A	10KA @ 125V/AC	125V
SBC520-015-__	15A		
SBC520-016-__	16A		
SBC520-020-__	20A		
SBC520-025-__	25A		
SBC520-030-__	30A		

└─ Style Options: Nil = Axial w/o Leads  
 PA = Axial with Leads  
 PR = Radial Bent Leads  
 ex. SBC520-3.15-PR