



Constructiion: Ceramic Tube
 Rated current: 0.1A-30A
 Rated Voltage: 125V/250V
 Standard: JIS C6575

Electrical Characteristic

Rated Current	1.3 In	1.6 In	2 In	20 In
In	Min.	Max.	Max.	Min.
100mA-30A	4 h	60min	120s	0.01s



TLC635 Series
Time-Lag, Ceramic Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
TLC635-0.100-__	100mA	35A @ 250V/AC 10KA @ 250V/AC	125V/250V
TLC635-0.125-__	125mA		
TLC635-0.160-__	160mA		
TLC635-0.200-__	200mA		
TLC635-0.250-__	250mA		
TLC635-0.300-__	300mA		
TLC635-0.315-__	315mA		
TLC635-0.400-__	400mA		
TLC635-0.500-__	500mA		
TLC635-0.600-__	600mA		
TLC635-0.630-__	630mA		
TLC635-0.700-__	700mA		
TLC635-0.800-__	800mA		
TLC635-001-__	1A		
TLC635-1.25-__	1.25A	100A @ 250V/AC 10KA @ 125V/AC	125V/250V
TLC635-1.50-__	1.5A		
TLC635-1.60-__	1.6A		
TLC635-002-__	2A		
TLC635-2.50-__	2.5A		
TLC635-003-__	3A		
TLC635-3.15-__	3.15A		
TLC635-3.50-__	3.5A		
TLC635-004-__	4A	200A @ 250V/AC 10KA @ 125V/AC	125V/250V
TLC635-005-__	5A		
TLC635-006-__	6A		
TLC635-6.30-__	6.3A		
TLC635-007-__	7A		
TLC635-008-__	8A		
TLC635-010-__	10A	1000A @ 125V/AC	125V
TLC635-012-__	12A		
TLC635-013-__	13A		
TLC635-015-__	15A	1000A @ 32V/AC/DC	32V
TLC635-016-__	16A		
TLC635-020-__	20A		
TLC635-025-__	25A		
TLC635-030-__	30A		

└─ Style Options: Nil = Axial w/o Leads
 P = Radial Straight Leads
 PA = Axial with Leads
 PR = Radial Bent Leads
 ex. *TLC635-3.15-PR*