



Construction: Glass Tube
 Rated current: 0.1A-30A
 Rated Voltage: 125V/250V
 Standard: JIS C6575

Electrical Characteristic

Rated Current	1.3 In	1.6 In	2 In	20 In
	Min.	Max.	Max.	Min.
0.1A-30A	4 h	3600 S	120 S	0.01 S



TLG520 Series
Time-Lag, Glass Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
TLG520-0.100-__	100mA	35A @ 250V/AC 10KA @ 250V/AC	125V/250V
TLG520-0.125-__	125mA		
TLG520-0.160-__	160mA		
TLG520-0.200-__	200mA		
TLG520-0.250-__	250mA		
TLG520-0.300-__	300mA		
TLG520-0.315-__	315mA		
TLG520-0.400-__	400mA		
TLG520-0.500-__	500mA		
TLG520-0.600-__	600mA		
TLG520-0.630-__	630mA		
TLG520-0.700-__	700mA		
TLG520-0.800-__	800mA		
TLG520-001-__	1A		
TLG520-1.25-__	1.25A		
TLG520-1.50-__	1.5A		
TLG520-1.60-__	1.6A		
TLG520-002-__	2A	100A @ 250V/AC 10KA @ 125V/AC	125V/250V
TLG520-2.50-__	2.5A		
TLG520-003-__	3A		
TLG520-3.15-__	3.15A		
TLG520-3.50-__	3.5A		
TLG520-004-__	4A		
TLG520-005-__	5A		
TLG520-006-__	6A	200A @ 250V/AC 10KA @ 125V/AC	125V/250V
TLG520-6.30-__	6.3A		
TLG520-007-__	7A		
TLG520-008-__	8A		
TLG520-010-__	10A		
TLG520-012-__	12A		
TLG520-013-__	13A		
TLG520-015-__	15A	1000A @ 32V/AC	32V
TLG520-016-__	16A		
TLG520-020-__	20A		
TLG520-025-__	25A		
TLG520-030-__	30A		

└─ Style Options: Nil = Axial w/o Leads
 P = Radial Straight Leads
 PA = Axial with Leads
 PR = Radial Bent Leads
 ex. TLG520-3.15-PR